

# VEHICLE INSPECTION SHEET

DATE: \_\_\_\_\_ PULL LOCATION: \_\_\_\_\_ Vehicle: \_\_\_\_\_

Pass	Needs Attention	DRIVELINE
		1 engine Mounts in good condition secure
		2 Harmonic Balancer SFI approved or shielded
		3 Blower Belt Shield(s) intact and secure
		4 block saver plate (3/16 steel or 3/4 aluminum)
		5 Engine Side Shields or hood shields fiberglass(min. 0.060 or better)
		6 Sufficient Blower Restraints in good working order
		7 Fuel System (Lines, tanks , pump, shut-off, injection, etc) no leaks and secure 3 way shut-off valve req. for diesel
		9 Exhaust/Headers (in an upward direction)
		10 Engine Couplers shielded

Clutch-Flywheel-Transmission-Driveline		
		1 Flywheel (Steel billet or aluminum)
		2 Clutch steel billet or aluminum no gray cast or ductile
		3 Bellhousing steel or titanium clutch adj hole only no clutch fork hole. Ag tractors without steel bellhousing must have a blanket around clutch area in good condition and secure
		4 Automatic Transmission Blanket secure in good condition
		5 Starter ring, shield or blanket
		6 Planetary transmission blanket (Lenco type)
		7 Positive Reverse Gear Lockout
		8 Driveshaft shielding or loops (5/16 steel, 3/8 aluminum)
		9 U-Joint shielding (5/16 steel, 3/8 aluminum)
		10 Driveline Brakes (5/16 STEEL, 3/8 aluminum)
		11 Neutral Start Operation

DRIVER PROTECTION		
		1 Min. 2 1/2 pound fire extinguisher within driver reach
		2 Firesuit , min. of 1 layer Nomax 3, or its equivalent
		3 Helmet in good condition
		4 Five or four point safety harness or other required
		5 Fire Wall - No holes allowed
		6 Seat - Stable and rigid in all directions
		7 Fenders - Tractors and Minis

## THROTTLE - IGNITION INTERRUPTER

A Throttle Linkage		
		1 Check for ease of operation
		2 Dual return to idle springs
		3 Toe Strap (if foot feed is used)
		4 Rear to forward direction of operation

# VEHICLE INSPECTION SHEET

DATE: \_\_\_\_\_ PULL LOCATION: \_\_\_\_\_ Vehicle: \_\_\_\_\_

Pass Needs  
Attention B

## IGNITION INTERRUPTER

- 1 Check kill switch location on rear of vehicle
- 2 Check kill switch operation
- 3 Kill switch must stop any electric fuel pumps
- 4 In cab or driver platform (kill switch, fuel shut-off)
- 5 Neutral Light - Rear and Drivers Compartment

## FRAME AND CHASSIS

- 1 Frame and body per class requirements
- 2 Wheelbase or max length center rear axle to the forward point  
8500 mod turbo - 13ft  
7700 light limited turbo - 13ft  
10000 pro farm - 13ft  
11000 hot farm - 13ft  
7800 modifieds - 14ft  
6000 classic - 135 inches  
4500 4x4 trucks - 135 inches  
6200 4x4 trucks - 135 inches  
6200 twd - 15ft  
minis
- 3 Weight Racks must be secured & good condition
- 4 Operational brakes in good condition no leaks

## HITCH AND STABILIZER BARS

- 1 Check hitch construction and mounting
- 2 Hitch must be solid and rigid in all directrons
- 3 Hitch to have a 3.75" X 3" inch hole
- 4 Front hitch suffient for lifting and towing
- 5 Safety Hitch must be suffient
- 6 Stabilizer Bars - tractors 10in - minis - 6in
- 7 Minimum length of hitch from centerline of rear axle  
tractors - 18in - minis - 6in - 4500 4x4 - 36in  
6200 4x4 - 36% of vehicle wheelbase
- 8 Hitch height per class requirements  
tractors & 4500 4x4 - 20" - minis - 13"  
6200 4x4 - 22" - 6200 TWD - 30"
- 9 No cam-type hitches or trick hitches

Driver/Owner - I warrant and quarantee that all internal clutch/flywheel components in this pulling vehicle equal or exceed the safety requirements as definded.

Signature: \_\_\_\_\_

Print name: \_\_\_\_\_